

AR321

CONTOUR ROTARY TRIM MOWER



- QUICK ADJUSTMENT DECKS
- TRUSTWORTHY KUBOTA ENGINE
- ZERO MAINTENANCE WET PARKING BRAKES

Jake's signature cut, trusted by generations is guaranteed with the AR321 contour rotary trim mower regardless of the terrain. The TRUEDECK™ Heavy-Duty Contouring Cutting Units will follow the contours of the golf course, giving it the after cut finish it deserves.

Fitted with a Trustworthy Kubota® Engine and Zero maintenance brakes, it make routine maintenance simple, giving you more time to spend on the turf.

CUT WIDTH
72"
(182.22CM)

CUT HEIGHT
0.75" - 3.5"
(19MM - 88MM)

CUTTING CAPACITY
4.5^{AC}
(1.83HA) / HR
AT 6MPH (10KM/H)

FUEL CAPACITY
7.6^{GAL}
(28.7L)

MOWER ENGINE
KUBOTA®
24.8HP
(18.6KW) DIESEL

TRANSPORT SPEED
8.7^{MPH}
(14KPH)



SINCERELY

Jake

For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946



Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.

© 2021 Textron Specialized Vehicles Inc.

AR321

CONTOUR ROTARY TRIM MOWER



ROPS as standard

Fully adjustable control arm with fingertip operator lift lower controls

Tilt steering

TrueDeck™ cutting decks

Mesh storage net

Easy-access service bay

3WD traction system

Maintenance free wet parking brakes



Trustworthy Kubota® engine



Jake's signature cut



Quick and easy deck adjustments

DECKS & CUTTING UNITS

NUMBER AND SIZE	3 x 27" (68.58cm) TrueDeck rotary cutting units
BLADE MATERIAL	Hardened, carbon steel alloy
DECK LIFT & LOWER	Armrest mounted switch
WEIGHT TRANSFER	Adjustable hydraulic, electronically activated operator control
DECK CONSTRUCTION	9-gauge, stamped modular deck construction

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Parallel-series "on demand" 3WD
DECK DRIVE	Fixed displacement hydraulic
HYDRAULIC SYSTEM	8.7 gal. (33L) capacity, full flow filtration (10 micron filter); GreensCare biodegradable oil.
SERVICE BRAKES	Dynamic braking through hydrostatic drive
PARKING BRAKES	Service-free electronic wet disc
STEERING	Hydraulic power steering with tilt wheel
MOWING SPEED	6.2mph (10km/h)
REVERSE SPEED	3.7mph (6km/h)

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	1986lb (901kg)
LENGTH (less catchers)	122" (3.10m)
OVERALL HEIGHT (ROPS up)	82" (2.06m)
WHEELBASE	61" (1.54m)
TRANSPORT WIDTH	77" (1.96m)
WORKING WIDTH	77" (1.96m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- Light kit
- Slick tires
- Canopy
- Mulching kit