



STAINLESS
STEEL

SPECIFICATIONS

- Overall Length: 203"
- Overall Height: 112"
- Overall Width: 132"
- Hopper Capacity: 200 cu. ft.
- Hopper Length: 108" (9 ft.)
- Hopper Width: 93" (7-3/4 ft.)
- Weight: 3800 lbs.
- Tires: 12.4 X 42"
- Adjustable Axle: 72" to 120"
- Ground Clearance:
 - 44" Under Spinners
 - 36" Under Frame
- Hydraulic On/Off Conveyor
- Gearbox Driven Dual Spinners
- 2 Speed Drive Conveyor
- Deflector Shield
- Roll Tarp Standard
- 540 RPM PTO Standard
- 5000 lb. Jack
- Safety Guard Around Spinners
- 8" Apron chain - Stainless Steel
- Stainless Steel Box, legs, & Apron

6 TON DRY FERTILIZER SPREADER

PERFECT FOR PRE, POST, AND IN SEASON APPLICATIONS

OPTIONS

- Variable Rate
- Scale Kit with Monitor
- 540 / 1000 RPM PTO
- Hydraulic Driven Spinner
- Bull Pull Hitch
- Light Kit

40' - 50' - 60'
SPREAD PATTERN



MOBILITY
BY DALTON AG



Dalton
AG PRODUCTS



Manufacturer of
Fertilizer Application Equipment

www.DaltonAg.com

602 E. Van Buren | Lenox, Iowa 50801 | 800.342.7498